9.6.1 Purpose

The purpose is to provide a **zone** for the **development** of a maximum of four ground oriented **dwelling** units in the form of **single detached**, **semi-detached**, **duplex**, **three-plex** or **four-plex housing** on urban services. The R5c sub-zoning district allows for **care centre**, **major** as an additional use. The R5h sub-zoning district allows for **home based business**, **major** as an additional use. (*Bylaw 5467*)

9.6.2 Primary Uses4

- care centre, major (use is only permitted with the R5c sub-zoning district)
- duplex housing
- four-plex housing
- group home, major
- semi-detached housing
- single detached housing
- three-plex housing
- seniors housing

9.6.3 Secondary Uses

- boarding rooms
- care centres, minor
- home based businesses, minor
- home based businesses, major (in single detached housing only) (use is only permitted with the R5h sub-zoning district)
- secondary suites (in single detached housing only)
- seniors assisted housing
- seniors supportive housing

9.6.4 Subdivision Regulations

- Minimum lot width is 20.0m, except it is 22.0m for a corner lot.
- Minimum lot depth is 30.0m.
- Minimum lot width for single detached housing is 14.0m, except it is 16.0m for a corner lot.
- Minimum lot area for single detached housing is 450m².
- Minimum lot area is 700m², except it is 800m² for a corner lot, or 10,000m² if not serviced by a community sewer system. (Bylaw 5339)

9.6.5 Party Wall Subdivision Regulations

Lot Type	Minimum Lot area		Minimum Lot Width	
	interior	corner	interior	corner
Semi-Detached Housing	350m ²	400m²	10.0m	12.0m
Three-Plex Housing	235m ²	285m²	7.0m	9.0m
Four-Plex Housing	175m²	225m²	7.0m	9.0m

9.6.6 Development Regulations

 Maximum site coverage is 40% and together with driveways, parking areas and impermeable surfaces shall not exceed 50%.

- Maximum floor space ratio is 0.6.
- Maximum height is the lesser of 10.0m or 2.5 storeys, except it is 4.5m for secondary buildings and secondary structures.
- Minimum front yard is 4.0m, except it is 6.0m for a garage or carport to the back of curb or sidewalk for a front entry garage, or it is 0.6m to the side of the garage and 2.6m to the front building façade for side-entry garage and driveway layouts.
- Minimum side yard is 2.0m for a 1 or 1.5 storey portion of a building or a secondary building or structure and 2.5m for a 2 or 2.5 storey portion of a building, except it is 4.0m from a flanking street unless there is a garage accessed from the flanking street, it is 4.0m or it is 2.6m to the building for a side-entry garage and driveway from a flanking street and at least 6.0m from the back of curb or sidewalk. Where there is no direct vehicular access to the rear yard or to an attached garage or carport, one side yard shall be at least 3.0m. The minimum side yard setback for shared interior party walls shall be 0.0m. The minimum side yard setback for single detached housing is 1.5m, except it is 4.0m from a flanking street unless there is a garage accessed from the flanking street, it is 4.0m or it is 2.6m to the building for a side-entry garage and driveway from a flanking street and at least 6.0m from the back of curb or sidewalk.
- Minimum rear yard is 6.0m for a 1 or 1.5 storey portion of a building and 7.5m for a 2 or 2.5 storey portion of a building, except it is 1.0m for secondary buildings.
- The maximum height of any vertical wall element facing a front, flanking or rear yard (including walkout basements) is the lesser of 6.5m or 2.5 storeys, above which the building must be set back at least 1.2m.
- Maximum density is 30 units per gross hectare (12 units/gross acre).
- Maximum four dwelling units located in a building, with each unit having a minimum width of 6.5m. (Bylaw 5339)

9.6.7 Other Regulations

- In order for bareland strata developments to be consistent with the character of the surrounding neighborhood, the strata plan shall be considered as one site for defining the overall use, density and site coverage.
- The above noted **subdivision** and **development** regulations shall be applied to each strata **lot** within the strata plan.
- A minimum area of 25m² of **private open space** shall be provided per **dwelling**.
- Where development has access to a rear lane, vehicular access to the development is only permitted from the rear lane.
- For seniors assisted housing, seniors housing and seniors supportive housing, a safe drop-off area for patrons shall be provided on the site.
- For strata developments, common recreation buildings, facilities and amenities may be included in the strata plan. Recreational buildings shall be treated as **secondary buildings** for the purpose of determining the **height** and **setbacks** of the **building** as specified in each **zone**.
- For multi-unit residential housing, one **office** may be operated for the soul purpose of the management and operation of the multi-unit residential **development**.
- In addition to the regulations listed above, other regulations may apply. These include the general **development** regulations of Section 4 (secondary **development**, **yards**, projections into **yards**, lighting, agricultural setbacks, etc.); the specific use regulations of Section 5; the **landscaping** and fencing provisions of Section 6; and, the parking and loading regulations of Section 7.
- As per Section 4.10.2 All buildings and structures, excluding perimeter fencing (garden walls and fences) on lots abutting City Roads as identified on Schedule "B" shall not be sited closer to the City Road than the setback as per the appropriate zone measured from the offset Rights of Way as illustrated on Schedule "B". (Bylaw 5440)